



NEXUS Contractor™ 70/25 Volt Commercial Speaker System



N | E | X | U | S
Contractor Series

Sold in Pairs
w/Mounting Brackets

Features	Benefits
Full-Range Frequency	Provides deep, low-frequency bass and crystal clear highs for plush sound.
Aluminum Back Can	Protects speaker's components from construction materials and elements while enhancing sound.
70/25 Volt Transformer	Gives installer their choice of a 70 volt or 25 volt application depending on municipality codes.
Wattage Selection Dial on Face Plate of Speaker	Makes selecting and adjusting the speaker's wattage tap as easy as a turn of a dial.
4-5 Different Wattage Selections for each of the 70 or 25 Volt Options	Select a custom setting for quiet, normal and loud sound environments.
Quick-Snap Terminal Connects	Pre-wire into terminals then just snap into speaker.
Metal Safety Loop for Securing	Permits a safety cable to be run through speaker for additional support.
8 Ohm Transformer Override	Quickly adapts unit as an 8 ohm speaker to be use in residential environments.
E-Z Mount Clamping Tabs	Provides secure back-mount clamping by fastening screws on speaker face.
Mounting Brackets Included	Custom-fitting, in-ceiling brackets provided for cost savings and rapid installation.
Beautiful Fine-Mesh Grille	Attractive grille blends seamlessly into any commercial decor.

The NEXUS Contractor™ Commercial Series Includes:	
Mounting brackets	Strain relief protector
All mounting hardware	Fine-mesh grilles with foam insert
Speaker paint mask	User manual

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880



N | E | X | U | S™
CONTRACTOR SERIES

NEXUS Contractor™ 70/25 Volt Commercial Speaker System

SP-4NXC/T 4" 70/25V Speaker System
SP-5NXC/T 5.25" 70/25V Speaker System
SP-6NXC/T 6.5" 70/25V Speaker System

Specifications

Item Code	SP-4NXC/T 4" 70/25V Commercial Speaker System	SP-5NXC/T 5.25" 70/25V Commercial Speaker System	SP-6NXC/T 6.5" 70/25V Commercial Speaker System
Woofer	4" Polypropylene-Coated Woofer with Rubber Surround	5.25" Polypropylene-Coated Woofer with Rubber Surround	6.5" Polypropylene-Coated Woofer with Rubber Surround
Tweeter	3/4" PEI Tweeter	3/4" PEI Tweeter	3/4" PEI Tweeter
Frequency	60Hz –20kHz	50Hz –20kHz	50Hz –20kHz
Wattage	10 Watts RMS/ 30 Watts Max	60 Watts RMS/ 120 Watts Max	60 Watts RMS/ 140 Watts Max
Sensitivity	86 db 1w/1m	89 db 1w/1m	90 db 1w/1m
Impedance	8 ohms	8 ohms	8 ohms
Transformer	70/25 Volt Transformer Dial	70/25 Volt Transformer Dial	70/25 Volt Transformer Dial
Transformer Settings	10w/ 5w/ 2.5w/ 1.2w & 8 ohms	60w/ 30w/ 10w/ 5w/ 2w & 8 ohms	60w/ 30w/ 10w/ 5w/ 2w & 8 ohms
Dimensions	8" Dia. x 8 1/2" D	9 3/4" Dia. x 8 1/8 " D	10" Dia. x 8 1/8 " D
Cut Out Dimension	7" Dia.	8 1/2" Dia.	9" Dia.
Weight	4.6 lbs. per speaker	6.8 lbs. per speaker	7.1 lbs. per speaker

N | E | X | U | S™
CONTRACTOR SERIES

Sold in Pairs. Mounting Brackets included

speco technologies™

For more information contact us at:
Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880